

9000 + 9000 BTU
9000 + 12000 BTU
12000 + 12000 BTU

9000 + 9000 + 9000 BTU
9000 + 9000 + 12000 BTU
9000 + 12000 + 12000 BTU



WI-FI

Rezistență degivrare

Racire: A++ SEER: 6.1 Incalzire: A+ SCOP: 4

Specificatii tehnice		2PE-18HR32-N	3PE-27HR32
Combinatia de unitati interne standard		09+09	09+09+09
O singura unitate		09, 12	09, 12
Doua unitati		09+09, 09+12, 12+12	09+09, 09+12, 12+12
Trei unitati		Nu	09+09+09, 09+09+12, 09+12+12
Tip control		Telecomanda	Telecomanda
Capacitate de racire	Btu/h	17400(4200~19100)	27000(9500~30000)
	W	5100(1230~5600)	7900(2800~8800)
Capacitate de incalzire	Btu/h	18000(4400~19600)	27000(8350~30000)
	W	5200(1290~5750)	7960(2450~8800)
SEER (Clasa)	W/W	6.1 (A++)	6.1 (A++)
SCOP (Clasa)	W/W	4.0 (A+)	4.0 (A+)
Nivel de zgomot externa (sound power)	dB(A)	65	67
Date electrice			
Alimentare		220-240V~/50HZ	220-240V~/50HZ
Domeniu de voltaj		V	165~265
Putere consumata	Racire	W	1545(280~2050)
	Incalzire	W	1333(280~2050)
Curent operare	Racire	A	7.5(1.3~10.5)
	Incalzire	A	6.2(1.3~10.5)
Consum anual de electricitate	Racire	KWh	293
	Average	KWh	1400
Sistem refrigerant			
Refrigerant/Incarcare		Gram	R32/1100g
Tip compresor			Rotary
Compresor			GMCC
Conectori			
Robineti inalta si joasa presiune	Lichid	Inches	1/4"
	Gaz	Inches	3/8"
Altele			
Dimensiuni nete (W x H x D)		mm	853x602x349
Greutate neta		kg	31

Model	Interior	In-09 WiFi	In-12 WiFi	
Tip		POMPA DE CALDURA	POMPA DE CALDURA	
Tip control		Telecomanda	Telecomanda	
Capacitate racire	Btu/h	9000	12000	
Capacitate incalzire	Btu/h	9000	12000	
Nivel zgomot (sound power) (S/H/ML/Mute)	dB(A)	50/47/43/35/32	50/47/43/35/32	
Nivel zgomot (sound pressure) (S/H/ML/Mute)	dB(A)	40/37/33/25/22	40/37/33/25/22	
Date electrice				
Alimentare		220-240V~/50HZ	220-240V~/50HZ	
Domeniu de voltaj		V	165~265	
Curent	Racire	A	0.2	
	Incalzire	A	0.2	
Putere consumata	Racire	W	35	
	Incalzire	W	35	
Sistem ventilator				
Debit interior		m3/h	550	
Tip ventilator interior			CROSS FLOW	
Conectori				
Conexiuni teava	Lichid	Inches	1/4"	
	Gaz	Inches	3/8"	
	Lungime maxima /unit internă		15m	15m
	Diferenta maxima de inaltime		10m	10m
	Greutate standard incarcata		5m/unitate internă	5m/unitate internă
	Incarcare suplimentara		15g/m	15g/m
Altele				
Dimensiuni nete (W x H x D)		Interna	mm	
Greutate neta		Interna	kg	

I feel

I set

Inverter



Sterilizare
la 56°C